



POWER TAKE-OFF SOLUTIONS



ALLISON TRANSMISSIONS

Each PTO is provided with a Cab Control Switch, Hose Kit and Hydraulic Tee



350 Series

1000, 2000, & 2400 Series Transmissions

No heat shield required

Average Torque 250 ft lb



360 Series

MD HD World Transmissions

No backlash adjustment required

Average Torque 330 fl lb



280 & 380 Series

MD HD World Transmissions

Constant Mesh & Hotshift

Average Torque 480 ft lb

Power Take-Off Unit Product Features

- New internal piston design for more even pressure on clutch pack with no gear clash when engaging.
- Anti rotating thrust washers eliminates housing ware.
- Lock sealer used on all bolts during assy of PTO.
- Grease installed in direct mounted pumps eliminates the need for the installer to pack the unit.
- Lower profile housing for easier installation on narrow chassis.
- Steel lube line for internal oiling
- Machine stop for shaft seal allowing it to stay square with the shaft eliminating new seal leaks
- Viton seals used throughout
- Metal Solenoid Protector
- Fully assembled PTO with only one hose and electric line to hook up for quicker installation
- Direct mount pumps comes standard with a 90 degree rotatable flange with both 2 and 4 bolt patterns.
- All weather electrical connectors



1500 Continental Blvd., Suite Z
Charlotte, NC 28273
Phone: (704) 295-7575
Fax: (704) 295-7574

www.hydreco.com