



PTO SOLUTIONS FOR HEAVY DUTY REQUIREMENTS



FULLER, MACK, SPICER, TTC, ZF-MERITOR

Each PTO built with the Maximum Torque Density (MTD) Advantage.



850/856 Series

Up To 510 Ft/lb Of Intermittent Torque

Can Be Built To Accommodate All 8 Bolt Openings On Transmission

Interchangeable Gear Sets Between Models

Heavy Duty Power Take-Off Unit Product Features

- Lowest profile and highest torque in the industry
- More ratio's available over the other brands
- Available in multiple output shaft options
- Single switch engagement need only on/off
- All gears are hobbled cut & shaved for quieter operation
- Rotatable flange for pump mounting
- Machine stop for shaft seal allowing it to stay square with the shaft eliminating new seal leaks
- Viton seals and O-rings thru out
- Anti rotation thrust washers eliminates housing ware
- Grease installed in direct mounted pumps shafts eliminating the need for the installer to pack the unit
- Lock sealer used on all bolts during assy of PTO
- Product range extensive with solutions for many hard to find Asian, European and American transmissions
- Only PTO with Maximum Torque Density (MTD)
- Full width gears and high strength components provide maximum strength without creating potential for damage to vital transmission components ensuring trouble-free long life for equipment.



1500 Continental Blvd., Suite Z
Charlotte, NC 28273
Phone: (704) 716-9023
Fax: (704) 295-7574

www.hydreco.com