
Technical Data Sheet



PA860 SERIES POWER TAKE-OFF

8 Bolt Single Gear Side Mounted PTO

The 860 series is a single reduction PTO designed for Hino M009 transmissions with an 8 bolt opening.

Continuing Hydreco Powauto's commitment to maximum torque output, this PTO achieves superior strength with minimum size and is economically priced.

Suits:


Hino M009 transmissions. (Refer to the eGuide Configurator on www.hydreco.com for confirmation and details)


Product Features

- Output 96.7% of Engine Speed (OD) Output 70.0% of Engine Speed (DD) For maximum torque output for pump operation.
- Air Shift Operated For ease of engagement.
- Single Gear Design For simple and smooth operation.
- Viton Seals For high temperature conditions.
- Tapered Roller Bearings For higher torque capacity.




Technical Data Sheet





Technical Specifications		
Ratings & Service Parts		
Torque	Nm / ft.lb	412/304
Power @ 500 rpm	kW / hp	21.5 / 28.9
Power @ 1000 rpm	kW / hp	4 3.0 / 57.8
Output Shaft Rotation		Opposite to Engine
Approximate Bare Mass	kg / Ib	14.0 / 30.8
Mounting Kit		MKIIIIA
Mounting Gasket Kit		GK031
Seal Kit - Mechanical Output		SK093
Seal Kit - Hydraulic Output		SK093A
Repair Kit - Mechanical Output		BK093
Repair Kit - Hydraulic Output		BK093A

PTO DESIGNATION CODES



Manufacturers Code 4

- A = With Pressure Switch
- B = With Mounting Kit
- C = With Mounting Kit & PTO Control Kit
- F = With Pressure Switch & Mounting Kit

Note: For full details refer to the owners manual or the eGuide configurator found at www.hydreco.com/solutions/ on-road



Doc: PA860-09/19

HYDRECO

ADVANCED HYDRAULIC TECHNOLOGIES

HYDRAULICS

POWAUTO

HYDRECO®