Technical Data Sheet



PUPB SERIES HYDRAULIC PISTON PUMP

High Pressure Axial Piston Pump

The P series axial piston pump is ideal for applications requiring high pressure and moderate flow. The design of the P series axial pump is optimised for performance and flow, especially at low speed.

Manufactured from rugged heat-treated materials, this product is well suited to high pressure applications such as cranes, aerial platforms, hook-lift loaders and garbage compactors.

Product Features

- **High Pressure**
 - Maximum performance of hydraulic systems.
- Bi rotational
 - No need to stock two models of each size.
- Versatile positioning
 - Can be placed in any one of four orientations.
- Available with Powauto '08' mount

To fit the standard range of Powauto PTO's.


POWAUTO




HYDRECO www.hydreco.com **POWAUTO** ADVANCED HYDRAULIC TECHNOLOGIES




Technical Data Sheet





PUMP DESIGNATION CODES

P Series



C = Combined Side & Rear **Technical Specifications** Pump Size

Pump Ratings					
		25	32	40	45
Displacement Range	cm³/rev	25.0	32.0	40.0	45.0
Rated Pressure	bar	320			
	psi	4650			
Peak Pressure	bar	370			
	psi	5370			
Operating Speeds	Min. Operational	200			
	Max. Continuous	2000			
Pump Port Sizes	Inlet	I 1/4" BSPP			
	Outlet	3/4" BSPP			
Approx. Bare Mass	kg	12.0			
Length 'A'	mm	277			
Length 'B'	mm	125			
Length 'C'	mm	69			
Seal Kit		SKP25C			

Important: Ensure the pump has been filled with oil prior to installation/startup.

Doc: PUPB-11/20

POWAUTO

DEDAVID BROWN





